



## AMBRA

Water-based decorative render based upon a vinyl emulsion  
INTERIOR



### DESCRIPTION

Paint with the highest decorative quality, giving a marble like, traditional finish.

It is especially suitable for big surfaces like halls, dining rooms and flats.

### FIELD OF USE

It is designed for interior decoration.

### TECHNICAL CHARACTERISTICS

- Aspect : Pasty.
- Colours : White, can be tinted with Teintes 2000 colorants.
- Spreading-rate : 2 m<sup>2</sup>/kg (2 coats), complies with ISO 23811 (2009).
- Density : 1.58 +/- 0.05 Kg/L à 25°C, complies with NM ISO2811-1(2008).
- Viscosity : 1000 poises +/- 200 à 25° C.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper.
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Using a roller, apply an even coat of Ambra over the surface.

Before the product dries, spread out the Ambra in all directions using a triangular plastic rendering tool. To reduce the risk of lapping problems, work in areas of 1 to 2 m<sup>2</sup>.

Leave the product for approximately twelve hours to dry. Using a blade or rendering tool, scratch the surface to remove any uneven product.

Apply a second coat of Ambra, without dilution. Ambra should be applied with a suitable trowel.

Wait for three or four hours, lightly sand the surface and clean-up with a wet cloth and then with the special trowel, accentuate the differences in colour to achieve the marble-like effect.

If the trowel is not plastic, it's necessary to protect the blade with a cloth, before using. The use of a steel trowel will leave grey marks on the surface of Ambra. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

### APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Do not dilute.

### DRYING TIME

12 Hours.

### RECOMMENDED SYSTEM (consult us)

#### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B805 or SP88	2
COLOVINYL 600	1
AMBRA	2
CIRAGE AMBRA or COLOCIRE (option)	1

### STORAGE

Two years in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures..

### PACKAGING

5 kg, 10 kg and 25 kg.

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.  
For more details, consult safety data sheet N° 18.

Edition : October 2016 by Colorado (10/16).  
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001