TECHNICAL DATA SHEET



COLOCIRE

Water- based protective wax INTERIOR

DESCRIPTION

COLOCIRE is a pasty, water- based protective wax. It is designed to protect and maintain the appearance of AMBRA and KSOUR by improving it's gloss and resistance properties.

FIELD OF USE

It is designed to protect and maintain the appearance of special effect finishes like AMBRA (for interior) and KSOUR (for exterior) by improving it's gloss and resistance properties.

TECHNICAL CHARACTERISTICS

- Aspect : Transparent, glossy.
- Colors : Semi-transparent.
- Spreading-rate : 12 to 15m²/800ml.
- Density : 1.00 +/- 0.05 Kg/L at 25°C.
- Viscosity : 380 poises (Brookfield) +/- 50 at 25° C.

SURFACE PREPARATION

Mix well before use. For easy application and optimum performance the surface needs to be clean, sound and dry before waxing.

APPLICATION PROPERTIES

Using a soft cloth apply the wax over the surface using circular movements.

Do not apply on cold wet walls below 5° C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

This product should be diluted with water (0 to 20%).

DRYING TIME

20 to 25 minutes. Washable 4 weeks after drying.

STORAGE

One year in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

800 ml.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the Safety Data Sheet N° 44.

Edition : June 2014 by Colorado (DC 28 D). This version replaces all previous editions.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001