



COLOXIM

Water-based varnish



DESCRIPTION

Water-based varnish based on a vinyl copolymer.

FIELD OF USE

Designed for the protection of coatings sensitive to the weather.

TECHNICAL CHARACTERISTICS

- Aspect : Satin or gloss.
- Colors : Transparent.
- Spreading-rate : 10 to 15 m²/Kg depending upon the porosity of the surface.
- Density : 1kg/l +/- 0.05 at 25°C.
- % Solids (by weight) : 35 +/- 2 %.
- Viscosity : 100 KU +/- 5 of KERBS viscometer.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

For easy application and optimum performance the surface to protect with COLOXIM needs to be clean.
Recommended application equipment : Brush, roller, brush or conventional spray.

Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%)

APPLICATION DETAILS OF USAGE

Dilution : Water

DRYING TIME

Drying at 20 °C and 60% of humidity :

- * Touch dry : 30 min.
- * Dry : 1 hour.
- * Recoatable after a minimum 8 hours.

STORAGE

One year in the closed original container, as delivered.
Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before to use.

PACKAGING

0,7 L, 3 L et 20 L.

HEALTH & SAFETY

This product is not classified as dangerous according to regulations.
For more details, consult the safety data sheet N° 64.