



DECOSAND

Water-based decorative coating INTERIOR



67E5D;BF;A@

DECOSAND M.A.T. is a water-based decorative effect finish with a metallic sand finish.

FIELD OF USE

It is designed for interior decoration, giving a colored, pearlescent effect on walls.

It is especially suitable for big surfaces like halls, dining rooms and flats.

TECHNICAL CHARACTERISTICS

- Aspect : Colored Pearlescent metallic effect. Contains grains of sand.
- Colors : See our catalogue.
- Spreading-rate : About 7.5 m²/Kg (9 m²/L +/- 1) in one single coat applied by brush or sponge, complies with ISO 23811 (2009).
- Density : 1.06 to 1.30 Kg/L +/- 0.05 depending upon the color at 25° C, complies with NM ISO2811-1(2008).
- Viscosity : 120 KU's +/- 5 at 25° C (Kreb Stormer), complies with ASTM D561 (1991).

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- *Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Using a brush, apply over COLOFONDO an even coat over the surface.

Using a roller, apply over COLOVINYL 600 an even coat over the surface.

Using the special ATF spatula, brush or sponge, apply DECOSAND M.A.T. in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to 2 m^2 in order to obtain the desired effect.

Do not apply on cold wet walls below 5° C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application (can be diluted with up to 5% of water)

DRYING TIME

Prepare the surface with one or two coats of Colofondo (preferably tinted) or COLOVINYL 600 and leave to dry for 12 hours :

Drying time at 20°C and 60% relative humidity :

- * Touch dry : 3 to 4 hours.
- * Dry: 24 hours.
- * Washable : 20 days.

RECOMMENDED SYSTEM (Consult us)

INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
PUTTYMAX	2
COLOFONDO	1
DECOSAND M.A.T.	1

STORAGE

24 months in the closed plastic container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. Keep away from heat / Sparks/ naked flames/ hot surfaces. Do not smoke.

PACKAGING

- * DECOSAND : 2.5 Kg.
- * COLOFONDO : 1.6 Liters.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 30.

Edition : October 2016 by Colorado (09/16). This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001

www.colorado.sa