



STUCCO KSOUR

Water-based decorative render giving a marble like finish
INTERIOR/EXTERIOR



DESCRIPTION

KSOUR is a water-based decorative render based upon an acrylic emulsion.
Contains a fungicide.

FIELD OF USE

It is designed for exterior decoration (due to its anti-fungal properties), giving a marble like, traditional finish. It has a high degree of whiteness and excellent scrub resistance.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty render.
- Colours : Blanc, teintes : see our catalogue.
- Spreading-rate : 3 to 4 m² / kg (2 Coats) complies with ISO 23811 (2009).
- Density : 1.54 +/- 0.05 Kg/L to 25°C, complies with NM ISO2811-1(2008).
- Viscosité : 1000 poises +/- 200 to 25°C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper.
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Using a roller, apply an even coat of Ksour over the surface.

Before the product dries, spread out the Ksour in all directions using a triangular plastic rendering tool. To reduce the risk of lapping problems, work in areas of 1 to 2m².

Leave the product for approximately seven hours to dry. Using a blade or rendering tool, scratch the surface to remove any uneven product.

Apply a second coat of Ksour, without dilution. KSOUR should be applied with a suitable trowel.

Wait for three or four hours and then with the special trowel, accentuate the differences in colour to achieve the marble-like effect.

If the trowel is not plastic, it's necessary to protect the blade with a cloth, before using. The use of a steel trowel will leave grey marks on the surface of Ksour. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application. Can be diluted with water.

DRYING TIME

- *1st coat : 12h.
- *2nd coat : 4h.

RECOMMENDED SYSTEM (consult us)

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505	2
COLOVINYL 600	1
STUCCO KSOUR	2

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20	1
COLOPRIM	1
COLOVINYL 600	1
STUCCO KSOUR	2

STORAGE

One year in the closed paint can, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

5 kg.

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.
Fore more details, consult the safety data sheet N° 21.

Edition : October 2016 by Colorado (10/16).
This version replaces all previous editions.

N.B : The changing needs of our customers as well as technical progress may lead us to change the characteristics of our products without notice and without liability.

COLORADO is certified ISO 9001, ISO 14001 & OHSAS 18001