



TOUAREG M.A.T.

Water-based metallic and pearlescent decorative finish
INTERIOR

DESCRIPTION

TOUAREG is a water-based acrylic copolymer decorative effect finish.

FIELD OF USE

Recommended for interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Colored, slightly Metallic and Pearlescent effect.
- Colors : See our catalogue.
- Spreading-rate : About 6 m²/L (in 2 coats).
- Density : 1.15 Kg/L +/- 0.05 depending upon the color to 25° C.
- Viscosity : 108 KU's +/- 10 à 25° C.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- * Sand vigorously with a Chiendent brush.
- * Sand with sandpaper
- * Remove the dust.
- * Wash with a water-jet if necessary.

APPLICATION PROPERTIES

Using a roller, apply an even coat of Fondo ATF (White) or Colofondo (Tinted) over the surface. Let the Colofondo dry for 12 hours.

Using the special short pile roller, apply Touareg (diluted with 20% of water) in all directions over the surface. To reduce the risk of lapping problems, work in areas of 1 to 2 m².

Leave the product to dry.before applying a second diluted coat (and if necessary a third coat) using the short pile roller. Using a blade or rendering tool, spread out the Touareg in order to obtain the special effect. Do not apply on cold wet walls below 5°C or conditions of high relative humidity (> 70%).

APPLICATION DETAILS FOR USAGE

Dilution : This product is ready for application.
Mix well before use. Depending upon the application method used, this product can be diluted with upto 20% of tap water.

DRYING TIME

Drying time at 20°C and 60% relative humidity:

- * Touch dry : 3 to 4 hours
- * Dry : 24 hours
- * Washable : 20 days

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
COLENDUIT EXTRA B505 ou SP88	2
COLOVINYL 600	1
COLOFONDO	1
TOUAREG M.A.T.	1

STORAGE

Six months in the closed plastic container, as delivered.
Store inside in conditions avoiding extremes of hot and cold temperatures..

PACKAGING

- *TOUAREG : 2.5 Liters.
- *COLOFONDO : 1,6 liters.
- *Mixing time : 1 minute

HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

Fore more details, consult the safety data sheet N° 65.