

## VERNIS DEKEAU

Pure acrylic varnish



### DESCRIPTION

Water-based varnish based on a pure acrylic resin. Vernis Dekeau is a water-based varnish, designed for the exterior protection of sensitive coatings and has excellent weather resistance, and good washability.

### FIELD OF USE

This varnish does not contain any dangerous solvent and is particularly adapted for high quality decoration inside and outside ( wood, concrete and P.V.C.) and recommended for the protection of decorative finishes on interior walls.

### TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colors : Transparent.
- Spreading-rate : 9 to 10 m<sup>2</sup>/Kg depending upon the porosity of the surface.
- Density : 1.05 +/- 0.05 at 25°C.
- Viscosity : 100 KU +/- 5 at 25°C.

### SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry before rendering :

- \* Sand vigorously with a Chiendent brush.
- \* Sand with sandpaper
- \* Remove the dust.
- \* Wash with a water-jet if necessary.

### APPLICATION PROPERTIES

Can be applied by a roller, brush or spray on clean and dry surface.

Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (> 70%)

### APPLICATION DETAILS OF USAGE

Dilution : 0 to 10% with water

### DRYING TIME

Drying at 20 °C and 60% of humidity :

- \* Touch dry : 30 min
- \* Dry : 1 hour.
- \* Recoatable after a minimum 8 hours.

### STORAGE

One year in the closed original container, as delivered. Store inside in conditions avoiding extremes of hot and cold temperatures. However, it is recommended to stir the product before use.

### PACKAGING

800 ml and 3 liters

### HEALTH & SAFETY

This product is not classified as dangerous under current regulations.

For more details, consult the safety data sheet N° 64.

Edition : June 2014 by Colorado (DC 28 D).  
This version replaces all previous editions.