



GLASS BRILLANT

Glossy transparent acrylic varnish
INTERIOR / EXTERIOR



DESCRIPTION

Varnish based on modified acrylic resins.

FIELD OF USE

Interior and exterior varnish, leaving a smooth, glossy film. It is particularly suitable for high quality decoration.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss and smooth
- Tint: Transparent.
- Spreading-rate : 12 - 14 m²/L..
- Density : 0.88 +/- 0.05 Kg/L at 25°C.
- Viscosity : 1 mn FC6 +/- 10 sec at 25°C.
- % weight solids: 36 +/- 2%.

SURFACE PREPARATION

For easy application and optimum performance the surface needs to be clean, sound and dry.

APPLICATION PROPERTIES

Recommended application equipment : Brush, roller and conventionel spray.
Application limit : Do not apply on cold, wet walls below 5°C or conditions of high relative humidity (>70%).

APPLICATION DETAILS OF USAGE

Dilution : D 66 (white spirit).

DRYING TIME

Drying at 20 °C and 60% of humidity :

- * Touch dry : 45 minutes.
- * Dry : 4 to 6 hours.
- * Recoatable after 24 hours.

STORAGE

One year in the closed original container, as delivered.
Store inside in conditions avoiding extremes of hot and cold temperatures.

PACKAGING

1 L and 5 L.

HEALTH & SAFETY

Flammable and harmful product.
For more details, consult the Safety data sheet N° 09.